27 5404281721

U.S. Patent Application No. 09/973,624 Amendment dated May 27, 2008 Reply to Office Action of February 27, 2008 RECEIVED
CENTRAL FAX CENTER
MAY 2 7 2008

## **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

- 1. (Canceled)
- 2. (Previously presented) A non-oxide powder of which at least about 40% by mass is comprised of a plurality of tightly agglomerated compositions, each of said tightly agglomerated compositions comprising a plurality of primary particles tightly agglomerated together, wherein said primary particles have an average size in a range of about 1 nanometer to about 500 nanometers, wherein for each tightly agglomerated composition, at least about 60% of its constituent primary particles are within 2.25dN<sup>1/3</sup> nanometers of at least about 60% of its other constituent primary particles, wherein N represents the number of primary particles in the tightly agglomerated composition, and wherein d represents the average size of the primary particles in the tightly agglomerated composition.
- 3. (Original) The non-oxide powder of claim 2 wherein said primary particles are selected from the group consisting of metals, intermetallics, metal matrix composites, ceramics, and non-metals.
- 4. (Original) The non-oxide powder of claim 3 wherein, for each tightly agglomerated composition, at least about 60% of its constituent primary particles are within 2.25dN<sup>1/3</sup> nanometers of all its other primary particles.
- 5. (Original) The non-oxide powder of claim 3 wherein, for each tightly agglomerated composition, at least about 50% of its constituent primary particles have sizes not deviating by more than a factor of 2 from the average size of its constituent primary particles, and at least about 90% of its constituent primary particles have sizes not deviating by more than a factor of 4 from the average size of its primary particles.

5404281721

- 6. (Original) The non-oxide powder of claim 3 wherein, for each tightly agglomerated composition, at least about 80% of its primary particles are within 2.25dN<sup>1/3</sup> nanometers of at least about 80% of its other primary particles.
- 7. (Original) The non-oxide powder of claim 3 wherein each of said tightly agglomerated compositions are comprised of at least 20 of said primary particles agglomerated together.
- 8. (Original) The non-oxide powder of claim 7 wherein, for each tightly agglomerated composition, at least about 60% of its primary particles are not closer than dN<sup>1/3</sup> nanometers of at least about 60% of its other primary particles.
- 9. (Original) The non-oxide powder of claim 3 wherein at least about 75% by mass of said powder is comprised of said tightly agglomerated compositions.
- 10. (Previously presented) The non-oxide powder of claim 3 wherein at least one of said tightly agglomerated compositions further comprises a secondary material within which the primary particles of said at least one agglomerated composition are encapsulated.
- 11. (Original) The non-oxide powder of claim 10 wherein said secondary material is selected from the group consisting of salts and polymers.
- 12. (Original) The non-oxide powder of claim 11 wherein each of said tightly agglomerated compositions further comprises a secondary material within which its primary particles are encapsulated.
- 13. (Original) The non-oxide powder of claim 11 wherein said powder has an encapsulation efficiency in the range of about 10% to about 99% by mass.

5404281721

- 14. (Original) The non-oxide powder of claim 13 wherein said powder has an encapsulation efficiency in the range of about 70% to about 99% by mass.
- 15. (Original) The non-oxide powder of claim 3 wherein said primary particles are selected from the group consisting of metals.
- 16. (Previously presented) The non-oxide powder of claim 15 wherein said primary particles are selected from the group consisting of valve metals.
- 17. (Original) The non-oxide powder of claim 16 wherein said primary particles are tantalum.
- 18. (Original) The non-oxide powder of claim 17 wherein each of said tightly agglomerated compositions has a specific surface area in the range of about 1 m<sup>2</sup>/g to about 70 m<sup>2</sup>/g.
- 19. (Original) The non-oxide powder of claim 16 wherein said primary particles are niobium.
- 20. (Original) The non-oxide powder of claim 15 wherein said primary particles are selected from the group consisting of refractory metals.
- 21. (Original) The non-oxide powder of claim 3 wherein said primary particles are selected from the group consisting of carbon and boron.
- 22. (Original) The non-oxide powder of claim 3 wherein said primary particles are selected from the group consisting of ceramics.
- 23. (Original) The non-oxide powder of claim 3 wherein said primary particles are selected from the group consisting of intermetallics.

- 24. (Original) The non-oxide powder of claim 3 wherein said primary particles are selected from the group consisting of metal matrix composites.
- 25. (Original) The non-oxide powder of claim 3 wherein said powder has a primary particle purity based on metal contaminants of less than about 10,000 parts per million by mass.
- 26. (Original) The non-oxide powder of claim 25 wherein said powder has a primary particle purity based on metal contaminants of less than about 1000 parts per million by mass.
- 27. (Original) The non-oxide powder of claim 26 wherein said powder has a primary particle purity based on metal contaminants of less than about 50 parts per million by mass.
- 28. (Previously presented) The non-oxide powder of claim 2 wherein said primary particles have an average size in a range of about 1 nanometer to about 100 nanometers

29-54 (Canceled)

55. (Previously presented) A powder comprising:

a plurality of primary particles, each primary particle having a size in the range of about 1 nanometer to about 500 nanometers; and

a secondary material within which at least some of said primary particles are encapsulated;

wherein a plurality of said primary particles are agglomerated together;

wherein between about 10% and about 100% of said primary particles are encapsulated in said secondary material;

wherein said primary particles are selected from the group consisting of metals, intermetallics, metal matrix composites, ceramics, and non-metals; and

wherein said secondary material is selected from the group consisting of salts and polymers.

- U.S. Patent Application No. 09/973,624 Amendment dated May 27, 2008 Reply to Office Action of February 27, 2008
- 56. (Original) The powder of claim 55 wherein said primary particles are selected from the group consisting of metals.
- 57. (Original) The powder of claim 56 wherein said primary particles are selected from the group consisting of valve metals.
- 58. (Original) The powder of claim 57 wherein said primary particles are tantalum.
- 59. (Original) The powder of claim 58 wherein said agglomeration of tantalum particles has a specific surface area in the range of about  $1 \text{ m}^2/\text{g}$  to about  $70 \text{ m}^2/\text{g}$ .
- 60. (Original) The powder of claim 56 wherein said primary particles are selected from the group consisting of refractory metals.
- 61. (Original) The powder of claim 55 wherein said primary particles are selected from the group consisting of carbon and boron.
- 62. (Original) The powder of claim 55 wherein said primary particles are selected from the group consisting of ceramics.
- 63. (Original) The powder of claim 55 wherein said primary particles are selected from the group consisting of intermetallics.
- 64. (Original) The powder of claim 55 wherein said primary particles are selected from the group consisting of metal matrix composites.
- 65. (Original) The powder of claim 55 wherein said secondary material is NaCl.
- 66. (Original) The powder of claim 55 wherein said secondary material is removable.

- 67. (Original) A capacitor-grade powder of which at least about 40% by mass is comprised of a plurality of tight agglomerations of primary particles, each tight agglomeration comprising at least 20 primary particles, said primary particles having an average size in the range of about 1 nanometer to about 200 nanometers and being selected from the group consisting of valve metals, wherein for each of said tight agglomerations, at least about 60% of its constituent primary particles are within 2.25dN<sup>1/3</sup> nanometers of at least about 60% of its other constituent primary particles, wherein N represents the number of primary particles in the same tight agglomeration, and wherein d represents the average size of said primary particles.
- 68. (Original) The capacitor-grade powder of claim 67 wherein said powder has a primary particle purity based on metal contaminants of less than about 1000 parts per million by mass.
- 69. (Original) The capacitor-grade powder of claim 67 wherein at least one of said tight agglomerations further comprises a secondary material within which the primary particles of that tight agglomeration are encapsulated, said secondary material being selected from the group consisting of salts and polymers.
- 70. (Original) The capacitor-grade powder of claim 67 wherein said powder has an encapsulation efficiency in the range of about 70% to about 100% by mass.
- 71-79 (Canceled)
- 80. (Previously presented) The non-oxide powder of claim 28 wherein said primary particles are selected from the group consisting of metals, intermetallics, metal matrix composites, ceramics, and non-metals.

- U.S. Patent Application No. 09/973,624 Amendment dated May 27, 2008 Reply to Office Action of February 27, 2008
- 81. (Previously presented) The non-oxide powder of claim 80 wherein each of said tightly agglomerated compositions are comprised of at least 20 of said primary particles agglomerated together.
- 82. (Previously presented) The non-oxide powder of claim 80 wherein at least about 75% by mass of said powder is comprised of said tightly agglomerated compositions.
- 83. (Previously presented) A non-oxide powder of which at least about 40% by mass is comprised of a plurality of tightly agglomerated compositions, each of said tightly agglomerated compositions comprising a plurality of primary particles tightly agglomerated together, wherein said primary particles have an average size in a range of about 1 nanometer to about 100 nanometers, wherein said primary particles are selected from the group consisting of metals, intermetallics, metal matrix composites, ceramics, and non-metals, and wherein at least one of said tightly agglomerated compositions further comprises a secondary material within which the primary particles of said at least one agglomerated composition are encapsulated.
- 84. (Previously presented) The non-oxide powder of claim 83 wherein said secondary material is selected from the group consisting of salts and polymers.
- 85. (Previously presented) The non-oxide powder of claim 84 wherein each of said tightly agglomerated compositions further comprises a secondary material within which its primary particles are encapsulated.
- 86. (Previously presented) The non-oxide powder of claim 85 wherein said powder has an encapsulation efficiency in the range of about 10% to about 99% by mass.
- 87. (Previously presented) The non-oxide powder of claim 86 wherein said powder has an encapsulation efficiency in the range of about 70% to about 99% by mass.

5404281721

- 88. (Previously presented) The non-oxide powder of claim 80 wherein said primary particles are selected from the group consisting of metals.
- 89. (Previously presented) The non-oxide powder of claim 88 wherein said primary particles are selected from the group consisting of valve metals.
- 90. (Previously presented) The non-oxide powder of claim 89 wherein said primary particles are tantalum.
- 91. (Previously presented) The non-oxide powder of claim 90 wherein each of said tightly agglomerated compositions has a specific surface area in the range of about 1  $m^2/g$  to about 70  $m^2/g$ .
- 92. (Previously presented) The non-oxide powder of claim 89 wherein said primary particles are niobium.
- 93. (Previously presented) The non-oxide powder of claim 88 wherein said primary particles are selected from the group consisting of refractory metals.

94-95 (Canceled)

- 96. (Previously presented) A non-oxide powder of which at least about 40% by mass is comprised of a plurality of tightly agglomerated compositions, each of said tightly agglomerated compositions comprising a plurality of primary particles tightly agglomerated together, wherein said primary particles have an average size in a range of about 1 nanometer to about 100 nanometers, wherein said primary particles are selected from the group consisting of intermetallics.
- 97. (Previously presented) A non-oxide powder of which at least about 40% by mass is comprised of a plurality of tightly agglomerated compositions, each of said tightly agglomerated

compositions comprising a plurality of primary particles tightly agglomerated together, wherein said primary particles have an average size in a range of about 1 nanometer to about 100 nanometers, wherein said primary particles are selected from the group consisting of metal matrix composites.

98-101 (Canceled)

- 102. (Previously presented) The non-oxide powder of claim 80 wherein at least one of said tightly agglomerated compositions further comprises a secondary material within which the primary particles of said at least one agglomerated composition are encapsulated.
- 103. (Previously presented) The non-oxide powder of claim 102 wherein said secondary material is selected from the group consisting of salts and polymers.
- 104. (Previously presented) The non-oxide powder of claim 103 wherein each of said tightly agglomerated compositions further comprises a secondary material within which its primary particles are encapsulated.
- 105. (Previously presented) The non-oxide powder of claim 104 wherein said powder has an encapsulation efficiency in the range of about 10% to about 99% by mass.
- 106. (Previously presented) The non-oxide powder of claim 105 wherein said powder has an encapsulation efficiency in the range of about 70% to about 99% by mass.
- 107. (Previously presented) The non-oxide powder of claim 80 wherein said primary particles are selected from the group consisting of carbon and boron.
- 108. (Previously presented) The non-oxide powder of claim 80 wherein said primary particles are selected from the group consisting of ceramics.

- U.S. Patent Application No. 09/973,624 Amendment dated May 27, 2008 Reply to Office Action of February 27, 2008
- 109. (Previously presented) The non-oxide powder of claim 80 wherein said primary particles are selected from the group consisting of intermetallics.
- 110. (Previously presented) The non-oxide powder of claim 80 wherein said primary particles are selected from the group consisting of metal matrix composites.
- 111. (Previously presented) The non-oxide powder of claim 80 wherein said powder has a primary particle purity based on metal contaminants of less than about 10,000 parts per million by mass.
- 112. (Previously presented) The non-oxide powder of claim 111 wherein said powder has a primary particle purity based on metal contaminants of less than about 1000 parts per million by mass.
- 113. (Previously presented) The non-oxide powder of claim 112 wherein said powder has a primary particle purity based on metal contaminants of less than about 50 parts per million by mass.
- 114. (Previously presented) The non-oxide powder of claim 28 wherein, for each tightly agglomrated composition, at least about 50% of its constituent primary particles have sizes not deviating by more than a factor of 2 from the average size of its constituent primary particles, and at least about 90% of its constituent primary particles have sizes not deviating by more than a factor of 4 from the average size of its primary particles.
- 115 (Previously presented) The non-oxide powder of claim 28 wherein the non-oxide powder is tantalum.
- 116 (Previously presented) The non-oxide powder of claim 114 wherein the non-oxide powder is tantalum.

- 117. (Previously presented) The non-oxide powder of claim 28 wherein the non-oxide powder is niobium.
- 118. (Previously presented) The non-oxide powder of claim 114 wherein the non-oxide powder is niobium.
- 119. (Canceled)